

Your barista arts
Your taste



F2 Introduction

You can always find a better machine, since the best one never exists. With the pursuit for a perfect cup of coffee, our commercial coffee expert F2 is born to make the coffee that reaches the professional barista level.

F2 Key Features

- The metallic body and brewer provide powerful guarantee for long life and high stability under the commercial condition.
- The pioneering brewing system can meet your need for both non-pressurized regular coffee and pressurized espresso.
- The innovative milk frothing system makes the foam very smooth, and it can be easily cleaned by its self-clean mechanism.
- Two grinders with ceramic flat-type blades accurately grind the coffee beans into unified-size powder, bringing out the unique flavor of the coffee.
- The 10.1" touch panel is easy to use, direct and efficient, by which customized coffee is just at your fingertips.

F2 Options

- 4L fridge and the cup warmer rack
- 2* 1kg independent powder dispensing system
- Telemetry control and E-payment system
- Specific rampway unit for grounds auto-disposing



F2 Capacity

Hourly output based on DIN18873-2

DR. COFFEE F2		
Advised daily output	250 cups	
Hourly output	Single	Double
Espresso	133	184
Regular Coffee	110	145
Cappuccino	85	115
Hourly hot water output	27L	
Water tank capacity	4L	
Beans hopper capacity	Approx. 2 * 1200 g	
Powder hopper capacity	Approx. 2 * 1000 g	
Grounds container capacity	Approx. 70 Pcs	

F2 Specifications

Coffee machine power supply and rated power	220-240V 50/60Hz 3.2-3.6KW
Fridge and cup warmer rack power supply and rated power	220-240V 50/60Hz 0.1-0.15KW
Plumbing type	G3/4' 150 cm flexible metal tube
Water pressure range	80-800KPa (0.8-8Bar)
Coffee machine dimension (W*D*H)	34 * 50 * 80 cm
Fridge and cup warmer rack Dimension (W*D*H)	31 * 43 * 64 cm
Weight (coffee machine / the fridge & cup warmer rack)	35 kg / 30 kg